

TIS Distribution Center  
CSP 4-18, X7712  
Syracuse, New York 13221

LEVEL 4  
GENERAL ELECTRIC

HEAVY MILITARY EQUIPMENT DEPARTMENT

TECHNICAL INFORMATION SERIES

5  
DDC  
NOV 14 1979  
RECEIVED

AA076489

Author W. Eugene Cramer	Subject Category Nuclear Explosion Effects	No. <u>R79EMH10</u> Date <u>10 Aug 1979</u>
Title NOMOGRAMS FOR OVERPRESSURE, FIREBALL RADIUS AND THERMAL ENERGY OF NUCLEAR WEAPONS		
Copies Available at HMED TIS Distribution Center Box 4840 (CSP 4-18) Syracuse, New York 13221	GE Class 1	No. of Pages 10
	Govt Class Unclassified	
<p>Summary</p> <p>The effects of nuclear explosions have been known for more than three decades, and phenomena that emit the largest portions of energy are the overpressure (blast wave) and thermal radiation. Nomograms are presented that quickly provide first-cut estimates of the emitted peak-exposure levels. These levels are then related to (1) the resulting damage effects of various structures and materials and (2) the biological effects on humans and animals.</p> <p>This document has been approved for public release and sale; its distribution is unlimited.</p>		

DDC FILE COPY

This document contains proprietary information of the General Electric Company and is restricted to distribution and use within the General Electric Company unless designated above as GE Class 1 or unless otherwise expressly authorized in writing.

408 969

9 14 11 088

Send to

## GENERAL ELECTRIC COMPANY TECHNICAL INFORMATION

Within the limitations imposed by Government data export regulations and security classifications, the availability of General Electric Company technical information is regulated by the following classifications in order to safeguard proprietary information:

### CLASS 1: GENERAL INFORMATION

Available to anyone on request.  
Patent, legal and commercial review  
required before issue.

### CLASS 2: GENERAL COMPANY INFORMATION

Available to any General Electric Company  
employee on request.  
Available to any General Electric Subsidiary  
or Licensee subject to existing agreements.  
Disclosure outside General Electric Company  
requires approval of originating component.

### CLASS 3: LIMITED AVAILABILITY INFORMATION

Original Distribution to those individuals with  
specific need for information.  
Subsequent Company availability requires  
originating component approval.  
Disclosure outside General Electric Company  
requires approval of originating component.

### CLASS 4: HIGHLY RESTRICTED DISTRIBUTION

Original distribution to those individuals personally responsible for the Company's interests in the subject.  
Copies serially numbered, assigned and recorded by name.  
Material content, and knowledge of existence, restricted to copy holder.

GOVERNMENT SECURITY CLASSIFICATIONS, when required, take precedence in the handling of the material. Wherever not specifically disallowed, the General Electric classifications should also be included in order to obtain proper handling routines.

GENERAL ELECTRIC COMPANY  
HEAVY MILITARY EQUIPMENT DEPARTMENT  
TECHNICAL INFORMATION SERIES

SECTION Reliability and Quality Assurance  
UNIT Systems Test and Evaluation Engineering  
HMED ACCOUNTING REFERENCE 463  
COLLABORATORS \_\_\_\_\_  
APPROVED E. H. Gibbons TITLE Mgr., ST&E LOCATION CSP 5-M2

TIS R79EMH10

MINIMUM DISTRIBUTION - Government Unclassified Material (and Title Pages) in G.E. Classes 1, 2, or 3 will be the following.

<u>Copies</u>	<u>Title Page Only</u>	<u>To</u>
0	1	Legal Section, HMED (Syracuse)
0	1	Manager, Technological Planning, HMED (Syracuse)
5	6	G-E Technical Data Center (Schenectady)

MINIMUM DISTRIBUTION - Government Classified Material, Secret or Confidential in G.E. Classes 1, 2, or 3 will be the following.

1	0	Manager, Technological Planning, HMED (Syracuse)
---	---	--

ADDITIONAL DISTRIBUTION (Keep at minimum within intent of assigned G.E. Class.)

<u>COPIES</u>	<u>NAME</u>	<u>LOCATION</u>
5 (CLASS 1 ONLY)	DEFENSE DOCUMENTATION CENTER	CAMERON STATION, ALEXANDRIA, VA. 22314
1	L. I. Chasen	P. O. Box 8555 Philadelphia, Pa., 19101
1	R. L. Benfey	CSP5 - M2
1	J. C. Buchta	CSP 4 - 58
1	G. P. Condon	GE - P. O. Box 8555 Philadelphia, PA
2	W. G. Cramer	CSP 5 - M2
1	F. A. Fisher	GE - Bldg. 5, Rm. 320 1 River Rd Schenectady, N. Y.
1	R. C. Fries	GE - P. O. Box 8555 Philadelphia, PA
1	H. A. Gamper, Jr.	GE - 37-679 Schenectady, N. Y.
1	E. H. Gibbons	CSP 5 - M2
1	S. W. Harris	GE - Rm 2563 Pittsfield, Mass.
1	C. M. Hewison	GE - 869 Road St., Mail Drop 624 Utica, N. Y.
1	Dr. G. H. Millman	CSP 4- 57
1	J. Peden	GE - P. O. Box 8555 Philadelphia, PA

<u>COPIES</u>	<u>NAME</u>	<u>LOCATION</u>
1	P. R. Rogers	GE - 37-679 Schenectady, N. Y.
1	B. H. Showalter	GE - P. O. Box 5000 Mail Drop 160 Binghamton, N. Y.
1	R. A. Taylor	CSP 5 - 8J
1	C. E. Titemore	CSP 5 - 7F
1	D. D. Ward	FRP 1 - 1D

Accession For	
REF	GM&I
DDC TAB	
Unannounced	<input checked="checked" type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or special
A	

## TABLE OF CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>
I	INTRODUCTION	1-1
II	OVERPRESSURE AND FIREBALL RADIUS	2-1
	2.1 Useage of Nomogram	2-1
	2.2 Damage and Overpressure	2-1
	2.3 Biological Effects	2-1
III	THERMAL ENERGY	3-1
	3.1 Useage of Nomogram	3-1
	3.2 Ignition of Materials	3-1
	3.3 Biological Effects	3-1

## GLOSSARY

cal	Calories
cm	Centimeter
km	Kilometer
kt	Kiloton
lb/in. <sup>2</sup>	Pounds per square inch
m	Meter
Mt	Megaton
P <sub>MAX</sub>	Maximum overpressure
psi	Pounds per square inch

## SECTION I

### INTRODUCTION

For more than 30 years it is known that the phenomena associated with nuclear weapon detonations have included ionizing radiation, electromagnetic pulse (EMP) effects, thermal radiation, overpressure and seismic waves. The characteristics of these phenomena are well documented in the literature, and one of the more accessible books is written by Samuel Glasstone.\* The nomograms on overpressure and thermal energy contained in this article are based on the data presented by Glasstone. However, new information is included concerning a "visibility" factor.

Nuclear weapons are similar to the more conventional types in so far as their destructive action is due mainly to blast or shock. However, there are several basic differences between nuclear and high-explosive weapons. First, nuclear explosions can be many thousands of times more powerful than the largest conventional detonations. Second, a fairly large porportion of the energy in a nuclear explosion is emitted in the form of light and heat, generally referred to as "thermal radiation". It is capable of causing skin burns and starting fires at considerable distances. Third, the nuclear explosion is accompanied by highly penetrating and harmful invisible rays, called the "initial nuclear radiation". Finally, the substances remaining after a nuclear explosion are radioactive, emitting similar radiations over an extended period of time. This is known as the "residual radioactivity".

The following paragraphs discuss two nomograms useful in visualizing the destructive aspects of nuclear explosions. These nomograms deal with the two phenomena delivering the largest energy fractions of the explosion yields, i. e., overpressure (included in blast and shock delivering 50%) and thermal radiation (35%).

---

\* Samuel Glasstone, The Effects of Nuclear Weapons, United States Atomic Energy Commission, Superintendent of Documents, US Government Printing Office, Washington, D. C., April 1962.

## SECTION II

### OVERPRESSURE AND FIREBALL RADIUS

#### 2.1 USEAGE OF NOMOGRAM

Nomograms are graphical representations that allow quick and convenient computation of an unknown from a set of given, known parameters. Figure 1 is a nomogram that enables estimation of the maximum overpressure and fireball radius from the yield (in tons of explosive force) and distance of a nuclear weapon. As an example it is desired to know the overpressure for a 20 kiloton (kt) weapon at a distance of 1 km from the detonation. By drawing a straight line from the 1-km point on the "range" scale to the 20 kt point on the "yield" scale, the intersects on the "maximum overpressure" scale is approximately 7 lb/in.<sup>2</sup> for the condition of a surface burst, or 14 lb/in.<sup>2</sup> for a burst occurring at optimum burst height. The fireball radius is found by drawing a horizontal line between the "yield" scale and the "maximum fireball radius" scale; for this example the maximum average fireball radius is approximately 0.24 km where the maximum burst height for negligible early fallout (radiation) is approximately 0.19 km (80% of maximum fireball radius). It is emphasized that this nomogram is useful in estimating any one of the parameters if the other two are known.

#### 2.2 DAMAGE AND OVERPRESSURE

Damage to various types of structures as a function of overpressure intensity is listed in table form in Figure 1. The structures range from glass windows to buried concrete arches, the most resistant to overpressure damage. Two relative descriptions of damage are given: (1) light, where the structure can readily be repaired; (2) heavy, where the structure is beyond or nearly beyond repair.

#### 2.3 BIOLOGICAL EFFECTS

A table is also given in Figure 1 that relates effects to humans and animals as a function of maximum overpressure ( $P_{MAX}$ ). If the maximum overpressure is greater than 5 lb/in.<sup>2</sup> (side-on or reflected overpressure), more than 1% of the exposed population will experience ruptured eardrums. Similarly, if  $P_{MAX}$  is greater than 45 lb/in.<sup>2</sup>, then better than 99% of the population will have ruptured eardrums. Overpressure ranges are also described for biological effects such as lung hemorrhage and the expected death rate (resulting largely from high yield weapons). The lower and upper limits on  $P_{MAX}$  correspond to the percentages of the exposed population that will experience a given destructive biological effect (in this case 1% and 99% boundaries).




Figure 1. Nomogram for Overpressure and Fireball Radius

### SECTION III

#### THERMAL ENERGY

##### 3.1 USEAGE OF NOMOGRAM

Thermal energy as a function of distance from the nuclear explosion is estimated using Figure 2 for a given visibility factor and weapon yield (tons of explosive force). As an example it is desired to estimate the thermal radiation for a 100-kt explosion at 10 km on a very clear day. The transmittance through the atmosphere is found by drawing a straight line between scale 1 (visibility) and scale 2 (range in km); the transmittance is read on scale 3 (approximately 0.4). Then, a straight line is drawn between 10 km on scale 4 and the 0.4 transmittance on scale 5 to find the intersect on scale 6. Between this intersect (scale 6) and 100 kt on scale 7, another straight line is drawn to find the thermal radiation ( $\text{cal/cm}^2$ ) on scale 8, i.e., about  $2 \text{ cal/cm}^2$ . Again, it is noted that this nomogram is useful in estimating any one of the parameters given the other three.

##### 3.2 IGNITION OF MATERIALS

The amount of thermal radiation required to start fires with various types of materials is listed in table form in Figure 2. The materials for which test data is given are paper, some organic materials (wood and grass) and some types of cloth.

##### 3.3 BIOLOGICAL EFFECTS

First degree burns are minor skin injuries similar to a sunburn with no blistering and will likely be experienced with a thermal radiation exposure of  $1 \text{ to } 2 \text{ cal/cm}^2$ . Second degree burns involve blistering and can be serious if the face or extensive parts of the body are exposed. This is experienced with a thermal radiation exposure of  $5 \text{ to } 10 \text{ cal/cm}^2$ . The extent of the injury is very much dependent upon the individual's skin tolerance to thermal energy and the shielding effect of clothing (tightness of weave and color).




Figure 2. Nomogram for Thermal Energy vs Distance